

Safer process.  
Safer profit.



# **rhenus** LKP 15 **PRODUCT INFORMATION**

Tried-and-tested pellet production



# rhenus LKP 15

## product information

**rhenus LKP 15 has been developed specifically for pellet production and as a result of its characteristics it is particularly suited to lubricating roller bearings, also for prolonged roller service life periods.**

rhenus LKP 15 is a special high-temperature grease that has produced excellent results when lubricating intensively used roller and sliding bearings. It is suitable for use at temperatures of up to 200°C and guarantees continuous relubrication. The grease's high levels of pressure stability guarantee outstanding long-term protection of the roller bearing.

The thickening agent and the additives used are highly temperature resistant and offer outstanding bearing integrity paired with good adhesive properties.

rhenus LKP 15 has been specifically geared towards high bearing temperatures and bearing pressures.

### Properties in detail:

- Highly resistant to thermal and mechanical stress
- Very resistant to ageing
- Good water resistance
- Very high pressure absorption capacity
- Highly mechanically stable
- Very good adhesion
- Good corrosion protection

**rhenus LKP 15 in the available consistency is very compatible for piping-based supply and thus it guarantees flawless roller bearing lubrication even when using a central lubrication system. In terms of lubrication the grease travels through the bearing very well and thus guarantees fresh grease at all bearing points.**

**The rhenus LKP 15 product range has produced excellent results in wooden pellet production.**

Rhenus Lub GmbH & Co KG  
Hamburgerring 45  
41179 Mönchengladbach, Germany

Telephone +49 2161 5869-0  
Fax +49 2161 5869-93

vertrieb@rhenusweb.de  
www.rhenuslub.com

Safer process.  
Safer profit.

